

Bestellnr.	max. übertragbares Motormoment (Nm) organischer Belag	max. übertragbares Motormoment (Nm) org. Spezialbelag	max. übertragbares Motormoment (Nm) Sinterbelag	solange Vorrat reicht
Reference-No.	<i>max. transmittable engine torque (Nm) organic facing</i>	<i>max. transmittable engine torque (Nm) org. special facing</i>	<i>max. transmittable engine torque (Nm) sintered plate</i>	<i>while stocks last</i>
88 3082 999 504	315	365	405	
88 3082 999 517	245	285	315	▲
88 3082 999 523	215	250	275	
88 3082 999 531	170	200	220	▲
88 3082 999 532	230	265	295	
88 3082 999 536	220	250	280	▲
88 3082 999 560	170	200	220	
88 3082 999 561	235	270	300	▲
88 3082 999 569	165	190	210	▲
88 3082 999 572	185	215	235	
88 3082 999 579	140	160	175	▲
88 3082 999 581	210	245	270	▲
88 3082 999 591	220	255	285	
88 3082 999 594	465	540	595	
88 3082 999 598	170	200	220	
88 3082 999 599	160	190	205	▲
88 3082 999 601	220	255	280	
88 3082 999 602	385	445	490	▲
88 3082 999 610	200	230	255	
88 3082 999 614	280	320	355	▲
88 3082 999 615	225	260	290	▲
88 3082 999 616	255	295	325	
88 3082 999 618	415	480	530	
88 3082 999 619	315	365	400	▲
88 3082 999 621	265	310	340	▲
88 3082 999 622	395	460	505	▲
88 3082 999 624	190	220	240	
88 3082 999 626	220	255	280	
88 3082 999 627	220	255	280	▲
88 3082 999 645	390	450	500	
88 3082 999 647	370	430	475	
88 3082 999 648	220	255	280	▲
88 3082 999 654	325	375	415	
88 3082 999 655	370	430	470	
88 3082 999 663	305	355	390	
88 3082 999 668	275	320	350	
88 3082 999 669	215	250	275	
88 3082 999 676	150	175	695	▲
88 3082 999 678	130	150	170	▲
88 3082 999 680	170	200	215	
88 3082 999 681	150	175	195	▲
88 3082 999 682	135	155	170	
88 3082 999 691	265	310	340	▲
88 3082 999 692	215	250	275	▲
88 3082 999 695	355	410	455	

Bestellnr.	max. übertragbares Motormoment (Nm) organischer Belag	max. übertragbares Motormoment (Nm) org. Spezialbelag	max. übertragbares Motormoment (Nm) Sinterbelag	solange Vorrat reicht
Reference-No.	<i>max. transmittable engine torque (Nm) organic facing</i>	<i>max. transmittable engine torque (Nm) org. special facing</i>	<i>max. transmittable engine torque (Nm) sintered plate</i>	<i>while stocks last</i>
88 3082 999 697	270	310	345	
88 3082 999 698	440	510	565	
88 3082 999 699	275	320	350	
88 3082 999 701	485	565	620	▲
88 3082 999 702	270	310	345	
88 3082 999 707	480	560	615	
88 3082 999 708	655	755	835	▲
88 3082 999 710	320	375	410	
88 3082 999 712	440	510	565	
88 3082 999 715	385	445	495	
88 3082 999 716	340	395	435	
88 3082 999 718	385	445	495	▲
88 3082 999 720	470	540	600	
88 3082 999 722	420	485	535	
88 3082 999 724	505	585	645	
88 3082 999 731	330	380	420	
88 3082 999 733	215	250	275	▲
88 3082 999 735	210	240	265	
88 3082 999 736	485	560	615	
88 3082 999 737	335	390	430	
88 3082 999 740	505	585	645	
88 3082 999 741	235	275	305	
88 3082 999 745	345	400	440	
88 3082 999 746	435	505	560	
88 3082 999 747	330	380	420	
88 3082 999 749	545	630	695	
06 3082 999 750	595	695	765	
88 3083 999 560	335	390	430	▲
88 3083 999 574	680	785	870	